

COVALENCE[®] S1182 ADHESIVE TAPE

Characteristics:	S1182 is a hotmelt adhesive material delivered on rolls.				
Applications:	S1182 is used as a filler material with PERP60E .Filler tape is used to fill the holiday thus restoring the mill applied coating thickness of the pipe.				
Product description:	S1182-XXXxYYYxZZZ XXX = Width in mm YYY = Thickness in mm ZZZ = Length in mm				
Material properties:	Typical Softening point : 94°C (201.2°F) acc ASTM E28 Typical Shear strength: 2.6 N/mm ² @ 23°C (73.4°F) acc ISO21809-3				
Dimensions:	Width: 50 mm (2") Thickness: 1 mm (0.039") Length per roll: 9000 mm (29.5 ft)				
Product printing & labeling:	No printing. Standard box labeling: Covalence Description, Part Number, Lotnumber, Quantity				
Ordering info:	S1182 rolls are packed in a box <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center; border-bottom: 1px solid black;">S1182-</th> <th style="text-align: center; border-bottom: 1px solid black;">Quantity per box</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">50X1X9000-RL</td> <td style="text-align: center;">24</td> </tr> </tbody> </table>	S1182-	Quantity per box	50X1X9000-RL	24
S1182-	Quantity per box				
50X1X9000-RL	24				

Information

Documentation	Extensive information is available on our web-site. Application instructions and other documentation can be obtained by contacting our head office, from our local distributor or by sending an email to info@sealforlife.com
Certified staff	Application of the described coating system should be carried out by certified personnel.